

Blackline H3T⁺

Three-way bi-amp/tri-amp trapezoid Hybrid™
fully horn loaded

features

- ▶ All-horn three-way system
- ▶ 'Phase-ball' loaded mid-driver
- ▶ Hybrid™ LF section
- ▶ Fitted with handles and castors
- ▶ Five year limited warranty

applications


- ▶ Larger club performance
- ▶ Large scale installs

The Blackline H3T⁺ is a very high performance, all-horn, three-way system in a single, wide-bandwidth package. New drivers have been developed for improved performance in all bands. The Hybrid™ low frequency section comprises a horn-loaded 15" (380mm)/4" (100mm) voice coil driver that is reflex loaded to extend the LF output to below the natural cut-off point of the horn. The new LF driver features a water resistant cone and triple roll surround for increased excursion.

The mid-horn of the H3T⁺ has a unique 'phase-ball' loading device which maintains the constant directivity characteristics of the horn at the upper end of its range. It is driven by a new 10" (250mm) midrange driver with an aluminium demodulating ring for improved high-mid clarity and reduced distortion when driven hard. The 70° x 40° HF section of the H3T⁺ features a neodymium 1" (25mm) exit compression driver with a Kapton diaphragm for high sensitivity and extended HF performance.

When driven in bi-amp mode, a Martin Audio M3⁺ Electronic Controller is available to provide H3T⁺ crossover and limiter facilities. A DX1 or equivalent controller is recommended for provision of crossover and limiter functions in tri-amp mode.

overall dimensions



technical specifications

TYPE	Three-way bi-amp/tri-amp trapezoid Hybrid™ fully horn loaded
FREQUENCY RESPONSE (5)	50Hz-18kHz ± 3dB
DRIVERS	15" (380mm)/4" (100mm) voice coil bass driver 10" (250mm)/2.5" (63.5mm) voice coil mid driver 1" (25mm) exit HF compression driver
RATED POWER (2)	LF: 750W AES, 3000W peak MF/(MF + HF): 300W AES, 1200W peak HF: 60W AES, 240W peak
RECOMMENDED AMPLIFIER	LF: 400-1500W into 4 ohms MF/(MF + HF): 400-800W into 4 ohms HF: 100-400W into 4 ohms
SENSITIVITY (6)	LF: 104dB, MF/(MF + HF): 104dB, HF: 106dB
MAXIMUM SPL (7)	131dB continuous, 137dB peak
NOMINAL IMPEDANCE	LF: 8 ohms, MF/(MF + HF): 8 ohms, HF: 8 ohms
DISPERSION (-6dB)	70° horizontal, 40° vertical
CROSSOVER	200Hz active, 2kHz active/passive
ENCLOSURE	250 litre, multi-laminate birch ply
FINISH	Textured black paint
PROTECTIVE GRILLE	Black perforated steel
CONNECTORS	2 x Neutrik NL8
PIN CONNECTIONS	LF +, - : 1 +, 1 -, MF/(MF + HF) +, - : 2 +, 2 - HF +, - : 3 +, 3 -, Link through all inc 4 +, 4 -
FITTINGS	12 x M10 inserts, 4 x 4" (100mm) castors 8 x pocket handles, 2 x lid clips
DIMENSIONS (inc wheels)	(W) 560mm x (H) 1066mm x (D) 780mm (911mm) (W) 22ins x (H) 42ins x (D) 30.7ins (35.9ins)
WEIGHT	77.5kg (170.5lbs)

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2007 Martin Audio Ltd.



www.martin-audio.com

professional